

# ROMULUS XL

Profile with IP65 diffusor  
Profil avec diffuseur IP65

A39104







**Puissance maxi Power max**  
35 w/m

**Dimensions Dimensions**  
20 x 11 mm

**Longueur maximale Max.length**  
3000 mm

**Fil incandescent Glow wire test**  
Night&Day 650°C - Opal/Frost/60° 850°C

**Température d'utilisation Ambient temp.**  
- 10°C / + 40°C



**A39104.C9.IP65.00.OP.DALI**

## Type of led

Pure CRI99	A4199	C99
UltraCRI	A4101	CR
Dynamic White	A4102	DW
Regular	A4109	C9
RGB	A4106	RGB
RGBW	A4107	RGBW
RGB2W	A4117	RGB2W
Ultra Efficiency 90	A4190	UE90
Ultra Efficiency 96	A4196	UE96

## IP Rating

IP20	IP20
IP54	IP54
IP65H	IP65

## Finishes

Aluminium anodised silver	00
Aluminium anodised black	04

## Cover & Optic

Opal	PC	OP
Frost	PC	FR
Transparent 60°	PC	T60
Night & Day	PC	ND

## Dimming

No dimming	HF
Dali	DALI
Dmx	DMX
Dimming 0/1-10V	D10



A39104.SQ  
Square optic



A39104.OP  
Optic Opal




A39104.ND  
Optic Night & Day



A39104.T60  
Optic Transparent 60°



A39104.SUS  
Suspension




A39104.00



A39104.FR  
Optic Frost



A39104.ECP60  
End cap for 60°



A39104.ECP  
End cap



A39104.CLI  
Clips