

CAMPUS HIGH HONEYCOMB

Profile with optic and honeycomb
 Profilé aluminium avec optique et grille nid abeille

A3961H



Puissance & largeur max Strip Led Power & width max Strip Led
 30 w/m - 12 mm



Dimensions Dimensions
 18 x 20 mm

Longueur maximale Max.length
 3000 mm

Leds/m minimum pour une ligne sans point led Minimum Leds/m for Dot-free (Opal cover)
 ≥ 180 leds/m

Température d'utilisation Ambient temp.
 - 10°C / + 40°C

HONEYCOMB OPTIC
 UGR<19



Optic 30°

18



A3961H.WX.IP20.00.HC30

Type of led

| | | |
|---------------------|-------|-------|
| Dim To Warm | A4126 | DTW |
| Dynamic White | A4102 | DW |
| Dynamic White COB | A4137 | COBDW |
| Full Spectrum | A4197 | SUN |
| Pixel RGB | A4120 | RGBX |
| Pixel RGBW | A4124 | RGBWX |
| Pixel Triple White | A4123 | 3WX |
| Pixel White | A4119 | WX |
| Pure CRI | A4199 | PCRI |
| Regular | A4109 | REG |
| Regular Mini Cut | A4159 | RMC |
| RGB | A4106 | RGB |
| RGB+W | A4107 | RGBW |
| RGB+2W | A4117 | RGB2W |
| Ultra CRI | A4101 | UCRI |
| Ultra CRI COB 10 | A4130 | COB10 |
| Ultra CRI COB 8 | A4130 | COB8 |
| Ultra Efficiency 90 | A4190 | UE90 |
| Ultra Efficiency 96 | A4196 | UE96 |
| Wine Protect | A4104 | WINE |

IP Rating

| | |
|-------------------|------|
| IP20 | IP20 |
| IP54 (Wet indoor) | IP54 |


Finishes

| | |
|---------------------------|-------|
| Aluminium anodised silver | 00 |
| Aluminium anodised black | 04 |
| Painting RAL (On request) | Rxxxx |

Cover & Optic

HoneyComb + Frost 30° PMMA 22% HC30

FROST 30° + HONEYCOMB



A3960.CAD
Adjustable clip



A3960.CLS
Stainless steel clip



A3960.JUN
Junction clip



A3960.C45
45° tilt clip



A3960.MAG
Fixing magnet