

# DYNAMIC WHITE COB

Tunable white led flex strip between 1800K & 6000K

Ruban led à blanc réglable de 1800K à 6000K

A4137



## Temperature de couleur CCT

1800K - 2100K - 2400K - 2700K - 3000K - 4000K - 5000K - 6000K

**Precision de couleur & IRC Color consistency & CRI**  
OneBinOnly | >90

**Rendement lumineux Luminous Efficacy (@4000K)**  
>107 lm/w

**Puissance & nombre de led Power & number of Led**  
10 w/m | 15 w/m & 576 chips/m


**Coupe Cutting unit**  
27.8 mm

**Dimensions Dimensions**  
5000 x 10 x 1.8 mm

**Tension d'alimentation & Classe isolation Input voltage & Class**  
24Vdc | class III

**Température d'utilisation Ambient temp.**  
- 20°C / + 50°C

## 10/15w



## Cutting unit



## A4137.15.576.918.930.IP20.DMX

### Power & number leds/m

15 w/m & 576 chips/m

10 w/m & 576 chips/m

### CCT & luminous flux/m

|       | 10w/m  | 15w/m  |     |
|-------|--------|--------|-----|
| 1800K | 480 lm | 700 lm | 918 |
| 2100K | 480 lm | 700 lm | 921 |
| 2400K | 500 lm | 730 lm | 924 |
| 2700K | 519 lm | 750 lm | 927 |
| 3000K | 540 lm | 800 lm | 930 |
| 4000K | 540 lm | 800 lm | 940 |
| 5000K | 580 lm | 850 lm | 950 |
| 6000K | 580 lm | 850 lm | 960 |
| 6500K | 614 lm | 881 lm | 965 |

For example : 2700K+4000K 15w/m = 750 lm+800lm=1550 lm

### IP Rating

IP20  
IP54 (Wet indoor)  
IP65H (Semi Outdoor)  
IP65T  
IP67T

### Dimming

Dali DT6  
Dali DT8  
DMX  
Casambi

IP20  
IP54  
IP65H  
IP65T  
IP67T

DALI6  
DALI8  
DMX  
CSB