


ULTRA OUTPUT 95

Linear strip with ultra output up to 5000 lm/m & up to 155 lm/w

Ruban ultra puissant jusqu'à 5000 lm/m & jusqu'à 155 lm/w

A4142



Temperature de couleur CCT

1800K - 2100K - 2200K - 2400K - 2700K
3000K - 3500K - 4000K - 5000K - 6000K 6500K

Precision de couleur & IRC Color consistency & CRI

OneBinOnly | >95

Rendement lumineux Luminous Efficacy (@4000K)

>155 lm/w

Puissance & nombre de led Power & number of Led

32 w/m & 240 leds/m

Coupe Cutting unit

33.3 mm

Dimensions Dimensions

3000 x 12 x 1.8 mm


Tension d'alimentation & Classe isolation Input voltage & Class

24 Vdc | class III

Température d'utilisation Ambient temperature

- 10°C / + 40°C

32w



Cutting unit



A4142.32.240.930.IP20.DMX

Power & number leds/m

32 w/m & 240 leds/m

Custom power on request

CCT & luminous flux/m

32w/m

1800K	>4020 lm
2100K	>4120 lm
2400K	>4280 lm
2700K	>4530 lm
3000K	>4780 lm
3500K	>4780 lm
4000K	>5030 lm
5000K	>4880 lm
6000K	>4880 lm
6500K	>4780 lm

32.240	918
	921
	924
	927
	930
	935
	940
	950
	960
	965

IP Rating

IP20

IP54 (Wet indoor)

Pour des IP supérieur, veuillez nous consulter
For higher IP ratings, please contact us.

IP20

IP54

Dimming

No dimming

Dali

Dmx

Dimming I to 10VDC

Casambi

HF

DALI

DMX

D10

CSB